





## TENSIONE DI RETE - TENSIONE COSTANTE 24 Vdc / MAIN VOLTAGE - CONSTANT LOW VOLTAGE 24 Vdc

	Codice Code	Voltaggio Voltage	Peso e dimensioni Weight and dimensions	Omologazioni Homologation	Rif. schema Scheme diagram
	<b>PSU.0005.0</b>	110÷264V <b>30W</b> 50/60Hz	200g 160x46x30 mm	<b>IP20</b> - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	<b>PSU.0006.0</b>	110÷264V <b>60W</b> 50/60Hz	410g 182x62x35 mm	<b>IP20</b> - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	<b>PSU.0020.0</b>	220÷240V <b>70W</b> 50/60Hz	290g 225x60x36 mm	<b>IP20</b> - CE KEMA KEUR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	<b>PSU.0007.0</b>	110÷264V <b>96W</b> 50/60Hz	520g 201x71x35 mm	<b>IP20</b> - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	<b>PSU.0012.0</b>	110÷264V <b>120W</b> 50/60Hz	650g 125x114x40 mm guida DIN / DIN rail	<b>IP20</b> - CE UL - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	<b>PSU.0017.0</b>	220÷240V <b>150W</b> 50/60Hz	320g 240x61x49 mm	<b>IP20</b> - CE KEMA KEUR SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	<b>PSU.0013.0</b>	110÷264V <b>240W</b> 50/60Hz	1030g 125x114x63 mm guida DIN / DIN rail	<b>IP20</b> - CE UL - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	<b>PSU.0014.0</b>	110÷264V <b>480W</b> 50/60Hz	1600g 125x129x86 mm guida DIN / DIN rail	<b>IP20</b> - CE UL - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	<b>PSU.0021.0</b>	110÷305V <b>320W</b> 50/60Hz	1900g 252x90x44 mm	<b>IP65</b> - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	<b>PSU.0008.0</b>	110÷264V <b>20W</b> 50/60Hz	220g 118x35x26 mm	<b>IP67</b> - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	<b>PSU.0015.0</b>	110÷305V <b>40W</b> 50/60Hz	440g 162,5x42,5x32 mm	<b>IP67</b> - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	<b>PSU.0016.0</b>	110÷305V <b>60W</b> 50/60Hz	440g 162,5x42,5x32 mm	<b>IP67</b> - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	<b>PSU.0009.0</b>	110÷295V <b>96W</b> 50/60Hz	1000g 222x68x39 mm	<b>IP67</b> - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	<b>PSU.0010.0</b>	110÷295V <b>150W</b> 50/60Hz	1000g 222x68x39 mm	<b>IP67</b> - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	<b>PSU.0018.0</b>	220÷240V <b>150W</b> 50/60Hz	600g 225x65x51 mm	<b>IP67</b> - CE KEMA KEUR SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	<b>PSU.0011.0</b>	110÷305V <b>240W</b> 50/60Hz	1300g 244x68x39 mm	<b>IP67</b> - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1






## 350 mA TENSIONE DI RETE - CORRENTE COSTANTE / 350 mA MAIN VOLTAGE - CONSTANT CURRENT

	Codice Code	Voltaggio Voltage	Peso e dimensioni Weight and dimensions	Omologazioni Homologation	N° Min - Max LED	Rif. schema Scheme diagram
	<b>PSU.0026.0</b>	220÷240V 50/60Hz	80g 125x38x23 mm	<b>IP20</b> - CE SELV - CLII	1-17 Power LED 1-4 High Power LED 1 COB LED 9,5 W	A1/B1
	<b>PSU.0027.0</b>	220÷240V 50/60Hz	50g 75x39x22,5 mm	<b>IP20</b> - CE - ENEC SELV - CLII	1-9 Power LED 1-2 High Power LED	A1
	<b>PSU.0023.0</b>	110÷264V 50/60Hz	100g 77x40x29 mm	<b>IP42</b> - CE SELV - CLII - UR	5-15 Power LED 1-4 High Power LED 1 COB LED 9,5 W	A1/B1
	<b>PSU.0024.0</b>	110÷264V 50/60Hz	220g 118x35x26 mm	<b>IP67</b> - CE CLII - UR	4-15 Power LED 1-4 High Power LED 1 COB LED 9,5 W	A1/B1
	<b>PSU.0025.0</b>	220÷240V 50/60Hz	80g 85x39x19 mm	<b>IP67</b> - CE SELV - CLII	1-12 Power LED 1-3 High Power LED 1 COB LED 9,5 W	A1/B1

## 350/500 mA MULTI CORRENTE-TENSIONE / 350/500 mA MULTI CURRENT-VOLTAGE

	<b>PSU.0030.0</b>	100÷240V 50/60Hz	108g 110x52x22 mm	CE - <b>IP20</b> KEMA KEUR SELV - cURus	DALI @ 350 mA: Max 13 Power LED Max 3 High power LED 1 COB LED 9,5 W @ 500 mA: Max 13 Power LED Max 3 High power LED 1 COB LED 14 W	A1/B1/C1/D1/ E1/F1/G1/H1/I1/ J1/K1/L1/M1/N1/ O1/P1
	<b>PSU.0001.0</b>	100÷240V 50/60Hz	124g 103x67x21 mm	CE - <b>IP20</b> KEMA KEUR SELV - UR	1-10 DIMMER & push button @ 350 mA: Max 15 Power LED Max 3 High power LED 1 COB LED 9,5 W @ 500 mA: Max 10 Power LED Max 2 High power LED 1 COB LED 14 W	A1/B1/C1/D1/ E1/F1/G1/H1/I1/ J1/K1/L1/M1/N1/ O1/P1

## 500 mA TENSIONE DI RETE - CORRENTE COSTANTE / 500 mA MAIN VOLTAGE - CONSTANT CURRENT

	<b>PSU.0003.0</b>	100÷240V 50/60Hz	35g 51x31x21 mm	<b>IP20</b> - CE KEMA KEUR SELV	1-3 Power LED 1 High Power LED	A1
	<b>PSU.0004.0</b>	110÷240V 50/60Hz	106g 111x38x28 mm	<b>IP20</b> - CE ENEC SELV	1-8 Power LED 1 High Power LED	A1
	<b>PSU.0022.0</b>	220÷240V 50/60Hz	80g 125x38x23 mm	<b>IP20</b> - CE SELV - CLII	1-13 Power LED 1-3 High Power LED 1 COB LED 14 W	A1/B1
	<b>PSU.0002.0</b>	100÷240V 50/60Hz	59g 52x30x23 mm	<b>IP66</b> - CE SELV - CLII cURus	1-3 Power LED 1 High Power LED	A1
	<b>PSU.0028.0</b>	110÷264V 50/60Hz	220g 118x35x26 mm	<b>IP67</b> - CE SELV - CLII cURus	3-10 Power LED 1-2 High Power LED 1 COB LED 14 W	A1/B1
	<b>PSU.0034.0</b>	110÷305V 50/60Hz	360g 148x40x32 mm	<b>IP67</b> - CE ENEC - UR CLII - SELV	10-15 Power LED 3 High Power LED 1 COB LED 14W-20W	A1/B1