








## Tensione di rete - tensione costante 24Vdc / Main voltage - constant low voltage 24Vdc

	<b>Codice Code</b>	<b>Voltaggio Voltage</b>	<b>Peso e dimensioni Weight and dimensions</b>	<b>Omologazioni Homologation</b>	<b>Rif. schema Scheme diagram</b>
	<b>PSU.0005.0</b>	110÷264V 30W 50/60Hz	200g 160x46x30 mm	IP20 - CE UR - SELV	C1-D1-E1-F1-G1- H1-I1-J1-K1-L1- M1-N1-O1-P1
	<b>PSU.0006.0</b>	110÷264V 60W 50/60Hz	410g 182x62x35 mm	IP20 - CE UR - SELV	C1-D1-E1-F1-G1- H1-I1-J1-K1-L1- M1-N1-O1-P1
	<b>PSU.0020.0</b>	220÷240V 70W 50/60Hz	290g 225x60x36 mm	IP20 - CE KEMA KEUR - SELV	C1-D1-E1-F1-G1- H1-I1-J1-K1-L1- M1-N1-O1-P1
	<b>PSU.0007.0</b>	110÷264V 96W 50/60Hz	520g 201x71x35 mm	IP20 - CE UR - SELV	C1-D1-E1-F1-G1- H1-I1-J1-K1-L1- M1-N1-O1-P1
	<b>PSU.0012.0</b>	110÷264V 120W 50/60Hz	650g 125x114x40 mm guida DIN / DIN rail	IP20 - CE UL - SELV	C1-D1-E1-F1-G1- H1-I1-J1-K1-L1- M1-N1-O1-P1
	<b>PSU.0017.0</b>	220÷240V 150W 50/60Hz	320g 240x61x49 mm	IP20 - CE KEMA KEUR SELV	C1-D1-E1-F1-G1- H1-I1-J1-K1-L1- M1-N1-O1-P1
	<b>PSU.0013.0</b>	110÷264V 240W 50/60Hz	1030g 125x114x63 mm guida DIN / DIN rail	IP20 - CE UL - SELV	C1-D1-E1-F1-G1- H1-I1-J1-K1-L1- M1-N1-O1-P1
	<b>PSU.0014.0</b>	110÷264V 480W 50/60Hz	1600g 125x129x86 mm guida DIN / DIN rail	IP20 - CE UL - SELV	C1-D1-E1-F1-G1- H1-I1-J1-K1-L1- M1-N1-O1-P1
	<b>PSU.0021.0</b>	110÷305V 320W 50/60Hz	1900g 252x90x44 mm	IP65 - CE UR - SELV	C1-D1-E1-F1-G1- H1-I1-J1-K1-L1- M1-N1-O1-P1
	<b>PSU.0008.0</b>	110÷264V 20W 50/60Hz	220g 118x35x26 mm	IP67 - CE UR - SELV	C1-D1-E1-F1-G1- H1-I1-J1-K1-L1- M1-N1-O1-P1
	<b>PSU.0015.0</b>	110÷305V 40W 50/60Hz	440g 162,5x42,5x32 mm	IP67 - CE UR - SELV	C1-D1-E1-F1-G1- H1-I1-J1-K1-L1- M1-N1-O1-P1
	<b>PSU.0016.0</b>	110÷305V 60W 50/60Hz	440g 162,5x42,5x32 mm	IP67 - CE UR - SELV	C1-D1-E1-F1-G1- H1-I1-J1-K1-L1- M1-N1-O1-P1
	<b>PSU.0009.0</b>	110÷264V 96W 50/60Hz	1000g 222x68x39 mm	IP67 - CE UR - SELV	C1-D1-E1-F1-G1- H1-I1-J1-K1-L1- M1-N1-O1-P1
	<b>PSU.0010.0</b>	110÷295V 150W 50/60Hz	1000g 222x68x39 mm	IP67 - CE UR - SELV	C1-D1-E1-F1-G1- H1-I1-J1-K1-L1- M1-N1-O1-P1
	<b>PSU.0018.0</b>	220÷240V 150W 50/60Hz	600g 225x65x51 mm	IP67 - CE KEMA KEUR SELV	C1-D1-E1-F1-G1- H1-I1-J1-K1-L1- M1-N1-O1-P1
	<b>PSU.0011.0</b>	110÷305V 240W 50/60Hz	1300g 244x68x39 mm	IP67 - CE UR - SELV	C1-D1-E1-F1-G1- H1-I1-J1-K1-L1- M1-N1-O1-P1




**350 mA tensione di rete - corrente costante / 350 mA main voltage - constant current**

	<b>Codice Code</b>	<b>Voltaggio Voltage</b>	<b>Peso e dimensioni Weight and dimensions</b>	<b>Omologazioni Homologation</b>	<b>N° Min - Max LED</b>	<b>Rif. schema Scheme diagram</b>
	<b>PSU.0026.0</b>	220÷240V 50/60Hz	80g 125x38x23 mm	IP20 - CE SELV - CLII	1-17 Power LED 1-4 High Power LED 1 COB LED 9,5 W	A1-B1
	<b>PSU.0027.0</b>	220÷240V 50/60Hz	50g 75x39x22,5 mm	IP20 - CE - ENEC SELV - CLII	1-9 Power LED 1-2 High Power LED	A1
	<b>PSU.0023.0</b>	110÷264V 50/60Hz	100g 77x40x29 mm	IP42 - CE SELV - CLII - UR	5-15 Power LED 1-4 High Power LED 1 COB LED 9,5 W	A1-B1
	<b>PSU.0024.0</b>	110÷264V 50/60Hz	220g 118x35x26 mm	IP67 - CE CLII - UR	4-15 Power LED 1-4 High Power LED 1 COB LED 9,5 W	A1-B1
	<b>PSU.0025.0</b>	220÷240V 50/60Hz	80g 85x39x19 mm	IP67 - CE SELV - CLII	1-12 Power LED 1-3 High Power LED 1 COB LED 9,5 W	A1-B1


**Multi corrente-tensione per Power LED max 350/500 mA  
Multi current-tension for Power LED max 350/500 mA**

	<b>PSU.0030.0</b>	100÷240V 50/60Hz	108g 110x52x22 mm	IP20 - CE KEMA KEUR - SELV - cURus	DALI @ 350 mA max 13 Power LED max 3 High Power LED 1 COB LED 9,5W @ 500 mA max 13 Power LED max 3 High Power LED 1 COB LED 14W	A1-B1-C1-D1- E1-F1-G1-H1- J1-K1-L1-M1- N1-O1-P1
	<b>PSU.0001.0</b>	100÷240V 50/60Hz	124g 124x78x22 mm	IP20 - CE KEMA KEUR - SELV - UR	1-10 dimmer & push button @ 350 mA max 15 Power LED max 3 High Power LED 1 COB LED 9,5W @ 500 mA max 10 Power LED max 2 High Power LED 1 COB LED 14W	A1-B1-C1-D1- E1-F1-G1-H1- J1-K1-L1-M1- N1-O1-P1


**500mA Tensione di rete corrente costante / 500mA Main voltage constant current**

	<b>PSU.0003.0</b>	100÷240V 50/60Hz	35g 51x31x21 mm	IP20 - CE KEMA KEUR SELV	1-3 Power LED 1 High Power LED	A1
	<b>PSU.0004.0</b>	110÷240V 50/60Hz	106g 111x38x28 mm	IP20 - CE ENEC - SELV	1-8 Power LED 1 High Power LED	A1
	<b>PSU.0022.0</b>	220÷240V 50/60Hz	80g 125x38x23 mm	IP20 - CE SELV - CLII	1-13 Power LED 1-3 High Power LED 1 COB LED 14 W	A1-B1
	<b>PSU.0002.0</b>	100÷240V 50/60Hz	59g 52x30x23 mm	IP66 - CE SELV - CLII cURus	1-3 Power LED 1 High Power LED	A1
	<b>PSU.0028.0</b>	110÷264V 50/60Hz	220g 118x35x26 mm	IP67 - CE SELV - CLII cURus	3-10 Power LED 1-2 High Power LED 1 COB LED 14 W	A1-B1
	<b>PSU.0034.0</b>	110÷305V 50/60Hz	360g 148x40x32 mm	IP67 - CE ENEC - UR CLII - SELV	10-15 Power LED 3 High Power LED 1 COB LED 14W-20W	A1-B1




**1 W 350 mA Controllo di corrente / 1 W 350 mA Current controller**

	<b>Codice Code</b>	<b>Voltaggio Voltage</b>	<b>Peso e dimensioni Weight and dimensions</b>	<b>Omologazioni Homologation</b>	<b>N° Min - Max LED</b>	<b>Rif. schema Scheme diagram</b>
	<b>ECG.0012.0</b>	24Vdc	10g Ø12x65 mm	CE - IP65 SELV	Min 1 - Max 5 Power LED max 1 High power LED dimmerabile <i>dimnable</i>	E1

**1,5 W 500 mA Controllo di corrente / 1,5 W 500 mA Current controller**

	<b>ECG.0014.0</b>	24Vdc	10g Ø12x65 mm	CE - IP65 SELV	Min 1 - Max 5 Power LED max 1 High power LED dimmerabile <i>dimnable</i>	E1
--	-------------------	-------	------------------	-------------------	---	----

**Inverter per elettroluminescenza / Electroluminescence inverter**

	<b>PSU.0031.0</b>	230V 5W 50Hz	20g 130xØ15 mm	CE - IP20	Max 2 m	Q1
	<b>PSU.0032.0</b>	230V 45W 50Hz	230g 140x70x39 mm	CE - IP20	Min 20 m - Max 40 m	Q1
	<b>PSU.0033.0</b>	230V 300W 50Hz	2600g 240x170x76 mm	CE - IP20	Min 200 m - Max 360 m	Q1

**Nota:**

Distanza massima tra inverter e modulo elettroluminescenza pari a 50m, con cavo da 2x1,5mm<sup>2</sup>, consumo strisce elettroluminescenti pari a 0,017W/cm<sup>2</sup>.

**Note:**

Maximum distance between inverter and electroluminescence module equal to 50m, with cable 2x1,5mm<sup>2</sup>, electroluminescence strips consumption equal to 0,017W/sqcm.